

About this course

This is a free self-study course outline written by Saving Planets. It is not a university course, it carries no academic credit, and no school is involved.

Its scope follows a one-semester junior engineering thermodynamics course. It is modeled on the topics and depth of MIT 16.050 Thermal Energy and the thermodynamics parts of MIT Unified Engineering (both free on MIT OpenCourseWare), and on courses such as Purdue ME 200 and Georgia Tech ME 3322, using the free OpenStax University Physics Volume 2 chapters on heat and the laws of thermodynamics and NIST's free fluid property data, which we link where they help. None of those authors or schools endorses this page.

What we add: every unit ties to real work with a cited public source (power-plant efficiency, nuclear and concentrating solar plants, heat pumps, combined heat and power and geothermal energy), every number on the page is re-computed by a checking script before it goes live, and every lab has a free simulation or a safe home version.

Work through it in order. Each unit has goals, key ideas, equations, step-by-step examples, practice with full answers, common mistakes, flashcards and a quiz. Your progress is saved only in this browser.

How this course helps save the planet

Almost all electricity from fuel, uranium, concentrated sunlight or Earth's heat comes from a thermodynamic cycle, and almost all heating and cooling runs on one too. The first law says energy is conserved; the second law says how much of it can become useful work. Between them they decide how much fuel the world burns.

Better cycles, recovered waste heat and heat pumps are some of the fastest ways to cut emissions. Each unit ends with a short, sourced section. Values that are not from a source are labeled as sample values.

Before you start

Prerequisites

- Calculus II and III: integrals, partial derivatives and natural logarithms.
- Physics I and General Chemistry I: energy, work, ideal gases and heat.
- Differential Equations is helpful but not required.

- Comfort with spreadsheets for tables and interpolation.

How to study

- Start every problem by drawing the system or control volume and saying whether it is closed or open, steady or not.
- List the known states and look up properties before writing any balance.
- Write the energy balance in words first (energy in – energy out = change in stored energy), then cancel terms you can justify.
- Keep units consistent: kJ, kPa, m³, kg and kelvin; never use °C inside a ratio of temperatures.
- Sketch every process on a T–s or p–v diagram; cycles become much easier to follow.
- Do every practice problem on paper before opening the answer, and retake the quizzes a few days later.

Lab equipment (for the wet labs)

- A computer or tablet for the free PhET Gas Properties, Energy Forms and Changes and States of Matter simulations.
- A kitchen thermometer (or a cheap digital probe), a measuring cup and a kitchen scale.
- An electric kettle with a known power rating, ice cubes, an insulated mug or foam cup.
- A phone stopwatch.
- Spreadsheet software for the cycle labs.

Suggested 15-week schedule

About 6 to 9 hours a week: reading, practice problems and, in lab weeks, the lab.

Week	Unit	Topics	Reading
1	Systems, Properties, Energy and Efficiency	Systems, properties, temperature, energy units, heat rate	OpenStax UP2 1.1, 3.1; EIA
2	Pure Substances, Phase Change and Property Tables	Phases, saturation, quality; Lab A	UP2 1.5, 2.1; NIST WebBook
3	Pure Substances, Phase Change and Property Tables	Steam tables, interpolation, ideal gas	NIST WebBook
4	Energy Transfer by Work and Heat	Boundary, shaft and electrical work; heat transfer modes; Lab D	UP2 3.2, 1.6
5	The First Law for Closed Systems	First law for closed systems, specific heats, latent heat; Labs B and C	UP2 3.3, 3.5
6	The First Law for Control Volumes: Steady-Flow Devices	Mass and energy for control volumes; nozzles, turbines, compressors	MIT 16.050

Week	Unit	Topics	Reading
7	The First Law for Control Volumes: Steady-Flow Devices	Throttles, mixing, heat exchangers; midterm practice	MIT 16.050
8	The Second Law: Heat Engines, Refrigerators and Carnot Limits	Second law, engines, heat pumps, Carnot; Lab E	UP2 4.2–4.5
9	Entropy and Isentropic Efficiency	Entropy, Clausius inequality, entropy generation	UP2 4.6–4.7
10	Entropy and Isentropic Efficiency	Isentropic processes and efficiencies	UP2 3.6; NASA Glenn
11	Exergy: How Much Energy Is Useful	Exergy, irreversibility, second-law efficiency	MIT 16.050
12	Gas Power Cycles: Otto, Diesel and Brayton	Otto and Diesel cycles	NASA Glenn
13	Gas Power Cycles: Otto, Diesel and Brayton	Brayton cycle, regeneration, combined cycles	NASA Glenn; MIT Unified
14	Vapor Power and Refrigeration Cycles	Rankine cycle and improvements	NIST WebBook
15	Vapor Power and Refrigeration Cycles	Refrigeration and heat pumps; Lab F; final practice	UP2 4.3

Your progress

Tick units and labs as you finish them, and take the quizzes. Progress and quiz scores are saved only in this browser, never sent to us.

Systems, Properties, Energy and Efficiency

Closed systems, control volumes and surroundings, properties and states, equilibrium and quasi-equilibrium processes, temperature scales and the zeroth law, pressure, forms of energy, energy units, and efficiency as useful output over required input.

Learning objectives

By the end of this unit you can:

- Choose a system or control volume and its boundary.
- Tell intensive from extensive properties, and state from path.
- Convert between kJ, kWh and Btu, and between °C and K.
- Compute an efficiency and a power plant's efficiency from its heat rate.

Key concepts

- A system is the region we study; a closed system exchanges energy but not mass with its surroundings, while a control volume (open system) lets mass cross its boundary.
- Properties such as pressure p , temperature T and specific volume $v = V/m$ describe the state. Intensive properties (p , T , v) do not depend on size; extensive ones (V , m , E) do. Two independent intensive properties fix the state of a simple compressible substance.
- The zeroth law: two bodies each in thermal equilibrium with a third are in equilibrium with each other; it is why thermometers work. Absolute temperature $T(K) = T(^{\circ}C) + 273.15$ must be used in every ratio and every gas law.
- Energy is stored as internal energy U , kinetic energy $\frac{1}{2}mV^2$ and potential energy mgz , and it crosses a boundary only as heat Q or work W .
- Efficiency = useful output $\div$ required input. For power plants, the U.S. EIA uses heat rate: Btu of fuel per kWh of electricity, with $1 \text{ kWh} = 3412 \text{ Btu}$.

Key equations

$$v = \frac{V}{m}, \quad \rho = \frac{1}{v}$$

Specific volume and density

$$T(K) = T(^{\circ}C) + 273.15$$

Absolute temperature

$$E = U + \frac{1}{2}mV^2 + mgz$$

Total stored energy

$$\eta = \frac{3412 \text{ Btu/kWh}}{\text{heat rate}}$$

Power-plant efficiency from heat rate (EIA)

Worked examples, step by step

Example 1.1 EIA gives heat rates of 10,500 Btu/kWh and 7,500 Btu/kWh as examples. Find each efficiency.

1. $\eta = 3412/10,500$.
2. $\eta = 3412/7500$.

Answer: 32.5% and 45.5% (EIA rounds these to 33% and 45%).

Example 1.2 A tank holds 2 kg of gas in 0.5 m³. Find v and ρ .

1. $v = 0.5/2$.
2. $\rho = 1/v$.

Answer: $v = 0.25 \text{ m}^3/\text{kg}$, $\rho = 4 \text{ kg/m}^3$.

Example 1.3 A 1000 kg car at 30 m/s brakes to a stop. How much kinetic energy becomes internal energy of the brakes, in kJ and kWh?

1. $\text{KE} = \frac{1}{2} \times 1000 \times 30^2 = 450,000 \text{ J}$.
2. $450 \text{ kJ} \div 3600 \text{ kJ/kWh}$.

Answer: $450 \text{ kJ} = 0.125 \text{ kWh}$.

Practice problems

Work each on paper first, then check.

1. Convert 25 °C to kelvin.

298.15 K.

2. Is temperature intensive or extensive?

Intensive.

3. A plant has a heat rate of 9000 Btu/kWh. Find its efficiency.

$$3412/9000 = 37.9\%.$$

4. Convert 1 MWh to GJ.

$$3600 \text{ MJ} = 3.6 \text{ GJ}.$$

Common misconceptions

Myth: Heat and temperature are the same thing.

Actually: Temperature is a property; heat is energy in transit.

Myth: A system “contains heat.”

Actually: It contains internal energy; heat exists only crossing a boundary.

Myth: Ratios can use °C.

Actually: Gas laws and efficiencies need kelvin.

Flashcards

System

Region under study.

Control volume

Mass can cross.

Specific volume

$$v = V/m.$$

Zeroth law

Basis of thermometers.

Heat rate

Btu per kWh.

1 kWh

$$3600 \text{ kJ} = 3412 \text{ Btu}.$$

Self-check quiz

1. A control volume allows...

mass to cross its boundary

no energy transfer

only heat

nothing

mass to cross its boundary. Open system.

2. Which is intensive?

volume

mass

pressure

energy

pressure. Independent of size.

3. A heat rate of 6824 Btu/kWh means efficiency of...

25%

50%

68%

100%

50%. $3412/6824$.

4. Energy crosses a closed-system boundary as...

mass

heat and work

temperature

pressure

heat and work. Only two ways.

Try this quiz again

How this helps save the planet

The U.S. Energy Information Administration measures power-plant efficiency with the heat rate: the fuel energy a plant uses to deliver one kilowatthour to the grid, counting the electricity the plant itself uses for fuel feeding, boiler pumps, cooling and pollution control. Dividing 3,412 Btu (the energy in one kWh) by the heat rate gives efficiency; EIA's examples are a 10,500 Btu plant at about 33% and a 7,500 Btu plant at about 45%.

That gap is the whole point of this course. For the same electricity, the 7,500 Btu plant burns $7,500/10,500 = 71.4\%$ as much fuel, so about 28.6% less fuel and CO₂. The laws of thermodynamics explain where the rest of the energy goes and how engineers claw some of it back.

On Saving Planets: [Solutions](#) · [Circuits](#)

Sources: [U.S. EIA: What is the efficiency of different types of power plants?](https://www.eia.gov/tools/faqs/faq.php?id=107&t=3) (<https://www.eia.gov/tools/faqs/faq.php?id=107&t=3>)

Free learning resources

- [OpenStax UP2, 1.1 Temperature and thermal equilibrium](https://openstax.org/books/university-physics-volume-2/pages/1-1-temperature-and-thermal-equilibrium) (<https://openstax.org/books/university-physics-volume-2/pages/1-1-temperature-and-thermal-equilibrium>): Free textbook section.
- [OpenStax UP2, 3.1 Thermodynamic systems](https://openstax.org/books/university-physics-volume-2/pages/3-1-thermodynamic-systems) (<https://openstax.org/books/university-physics-volume-2/pages/3-1-thermodynamic-systems>): Free textbook section.
- [MIT OpenCourseWare 16.050 Thermal Energy \(Fall 2002\)](https://ocw.mit.edu/courses/16-050-thermal-energy-fall-2002/) (<https://ocw.mit.edu/courses/16-050-thermal-energy-fall-2002/>): MIT thermal energy notes.
- [NASA Glenn: First law of thermodynamics](https://www.grc.nasa.gov/www/k-12/airplane/thermo1.html) (<https://www.grc.nasa.gov/www/k-12/airplane/thermo1.html>): Free NASA page.



I finished this unit

Pure Substances, Phase Change and Property Tables

Phases and phase change, saturation temperature and pressure, compressed liquid, saturated mixture and superheated vapor, quality, T–v and p–v diagrams, steam tables and interpolation, the ideal-gas equation and when it applies, and the compressibility factor.

Learning objectives

By the end of this unit you can:

- Identify the phase from p and T using saturation data.
- Use quality to find v, u and h of a saturated mixture.
- Interpolate in property tables.
- Use the ideal-gas law and know when it fails.

Key concepts

- A pure substance has a fixed chemical makeup. At a given pressure, water boils at one saturation temperature (99.61 °C at 100 kPa); while it boils, p and T stay fixed and the mixture's quality $x = m_{\text{vapor}}/m_{\text{total}}$ grows from 0 to 1.
- For a saturated mixture any specific property is $y = y_f + x(y_g - y_f) = y_f + x \cdot y_{fg}$, using saturated-liquid (f) and saturated-vapor (g) values from the tables.
- If T is below the saturation temperature at that pressure, the water is a compressed liquid (approximately saturated liquid at T); if above, it is superheated vapor, found in separate tables.
- Linear interpolation: $y = y_1 + (x - x_1)(y_2 - y_1)/(x_2 - x_1)$. NIST's free WebBook gives the same data for water and many refrigerants.
- At low pressure and high temperature relative to the critical point, gases obey $pv = RT$ with $R = R_u/M$; for air $R = 0.287 \text{ kJ}/(\text{kg} \cdot \text{K})$. Near saturation (steam in a boiler) use the tables instead.

Key equations

$$x = \frac{m_g}{m_f + m_g}$$

Quality

$$y = y_f + x y_{fg}$$

Saturated-mixture property

$$pv = RT, \quad R = \frac{R_u}{M}$$

Ideal-gas law

$$y = y_1 + \frac{x - x_1}{x_2 - x_1}(y_2 - y_1)$$

Linear interpolation

Worked examples, step by step

Example 2.1 At 100 kPa, $h_f = 417.51$ and $h_{fg} = 2257.5$ kJ/kg, $v_f = 0.001043$ and $v_g = 1.6941$ m³/kg (steam tables). Find h and v at quality 0.6.

1. $h = 417.51 + 0.6 \times 2257.5$.
2. $v = 0.001043 + 0.6 \times (1.6941 - 0.001043)$.

Answer: $h = 1772.0$ kJ/kg; $v = 1.0169$ m³/kg.

Example 2.2 Find the mass of air in a 0.5 m³ tank at 100 kPa and 300 K.

1. $m = pV/(RT) = 100 \times 0.5/(0.287 \times 300)$.

Answer: $m = 0.581$ kg.

Example 2.3 Find the pressure of 2 kg of air in 0.5 m³ at 400 K.

1. $p = mRT/V = 2 \times 0.287 \times 400/0.5$.

Answer: $p = 459.2$ kPa.

Practice problems

Work each on paper first, then check.

1. Water at 100 kPa and 80 °C is...

Compressed liquid (80 °C < 99.61 °C).

2. Water at 100 kPa and 150 °C is...

Superheated vapor.

3. Interpolate h at 25 °C if $h = 83.9$ at 20 °C and 125.7 at 30 °C (kJ/kg, saturated liquid).

$$83.9 + 0.5 \times 41.8 = 104.8 \text{ kJ/kg.}$$

4. Find R for helium ($M = 4.003 \text{ kg/kmol}$).

$$8.314/4.003 = 2.077 \text{ kJ/(kg}\cdot\text{K)}.$$

Common misconceptions

Myth: Temperature rises while water boils.

Actually: At constant pressure it stays at T_{sat} until all the liquid is gone.

Myth: Steam in a boiler is an ideal gas.

Actually: Near saturation it is not; use steam tables.

Myth: Quality applies to superheated vapor.

Actually: Only to saturated mixtures, $0 \leq x \leq 1$.

Flashcards

Saturation

Liquid and vapor coexist at $T_{\text{sat}}(p)$.

Quality

$$x = m_g/m.$$

Mixture property

$$y_f + x y_{fg}.$$

Compressed liquid

$$T < T_{\text{sat}}.$$

Superheated

$$T > T_{\text{sat}}.$$

Ideal gas

$$pv = RT.$$

Self-check quiz

1. Quality is...

vapor mass over total mass

liquid mass over total

temperature ratio

pressure ratio

vapor mass over total mass. $x = m_g/m$.

2. Water at 100 kPa and 120 °C is...

compressed liquid

saturated mixture

superheated vapor

solid

superheated vapor. Above T_{sat} .

3. R for air is about...

8.314

0.287

1.005

4.18

0.287. kJ/(kg·K).

4. During boiling at constant p, T...

rises

falls

stays constant

oscillates

stays constant. Saturation.

Try this quiz again

How this helps save the planet

The U.S. Department of Energy explains that nuclear reactors use fission heat to make steam that spins a turbine. All U.S. commercial reactors are light-water reactors: more than 65% are pressurized-water reactors, which keep core water under high pressure so it does not boil and make steam in a separate heat exchanger, and roughly a third are boiling-water reactors, which make steam directly in the vessel.

Both designs are exercises in this unit: raising the pressure raises the saturation temperature so water stays liquid, and the steam's quality and enthalpy set how much work the turbine gets. DOE counts more than 400 commercial reactors worldwide, including 94 in the United States, all built on steam tables.

On Saving Planets: [Solutions](#) · [General Chemistry I](#)

Sources: [U.S. DOE: Nuclear 101: How does a nuclear reactor work? \(May 2025\)](#) (<https://www.energy.gov/ne/articles/nuclear-101-how-does-nuclear-reactor-work>) · [NIST Chemistry WebBook: Thermophysical properties of fluid systems](#) (<https://webbook.nist.gov/chemistry/fluid/>)

Free learning resources

- [NIST Chemistry WebBook: Thermophysical properties of fluid systems](https://webbook.nist.gov/chemistry/fluid/) (<https://webbook.nist.gov/chemistry/fluid/>): Free steam tables.
- [OpenStax UP2, 1.5 Phase changes](https://openstax.org/books/university-physics-volume-2/pages/1-5-phase-changes) (<https://openstax.org/books/university-physics-volume-2/pages/1-5-phase-changes>): Free textbook section.
- [OpenStax UP2, 2.1 Molecular model of an ideal gas](https://openstax.org/books/university-physics-volume-2/pages/2-1-molecular-model-of-an-ideal-gas) (<https://openstax.org/books/university-physics-volume-2/pages/2-1-molecular-model-of-an-ideal-gas>): Free textbook section.
- [PhET: States of Matter](https://phet.colorado.edu/en/simulations/states-of-matter) (<https://phet.colorado.edu/en/simulations/states-of-matter>): Phase change interactively.



I finished this unit

Energy Transfer by Work and Heat

Sign conventions, boundary work and its area on a p–V diagram, constant-pressure, isothermal and polytropic processes, shaft and electrical work, and the three modes of heat transfer: conduction, convection and radiation.

Learning objectives

By the end of this unit you can:

- Compute boundary work for common processes.
- Show that work and heat are path functions.
- Compute shaft and electrical work and power.
- Estimate conduction and convection heat rates.

Key concepts

- Sign convention: heat into the system and work done by the system are positive (Q_{in} , W_{out}). Both are path functions: they depend on the process, not just the end states.
- Boundary work $W_b = \int p \, dV$ is the area under the process curve on a p–V diagram. At constant pressure $W_b = p(V_2 - V_1)$.
- For an ideal gas at constant temperature, $W_b = mRT \ln(V_2/V_1)$. For a polytropic process $pV^n = \text{constant}$ ($n \neq 1$), $W_b = (p_2V_2 - p_1V_1)/(1 - n)$.
- Shaft work: power = torque $\times$ angular speed, $\dot{W} = 2\pi\dot{n}T$. Electrical work: $W = VI\Delta t = P\Delta t$.
- Heat moves by conduction ($\dot{Q} = kA\Delta T/L$ through a wall), convection ($\dot{Q} = hA\Delta T$ to a moving fluid) and radiation ($\dot{Q} = \epsilon\sigma A(T_s^4 - T_{surr}^4)$). Insulation lowers k ; this is why building envelopes matter.

Key equations

$$W_b = \int_1^2 p \, dV$$

Boundary work

$$W_b = mRT \ln \frac{V_2}{V_1}$$

Isothermal ideal gas

$$W_b = \frac{p_2V_2 - p_1V_1}{1 - n}$$

Polytropic process

$$\dot{Q} = \frac{kA \Delta T}{L}, \quad \dot{Q} = hA \Delta T$$

Conduction and convection

Worked examples, step by step

Example 3.1 1 kg of air expands isothermally at 300 K to twice its volume. Find the work.

$$1. W = 1 \times 0.287 \times 300 \times \ln 2.$$

Answer: $W = 59.7 \text{ kJ}$ (done by the gas).

Example 3.2 Air is compressed polytropically ($n = 1.3$) from 100 kPa and 0.2 m^3 to 0.1 m^3 . Find p_2 and the work.

$$1. p_2 = 100 \times 2^{1.3} = 246.2 \text{ kPa}.$$

$$2. W = (246.2 \times 0.1 - 100 \times 0.2)/(1 - 1.3).$$

Answer: $p_2 = 246.2 \text{ kPa}$; $W = -15.4 \text{ kJ}$ (work done on the gas).

Example 3.3 A wall of area 10 m^2 , thickness 0.1 m and $k = 0.04 \text{ W/(m}\cdot\text{K)}$ (sample insulation) has 20 K across it. Find the heat loss.

$$1. \dot{Q} = 0.04 \times 10 \times 20/0.1.$$

Answer: $\dot{Q} = 80 \text{ W}$.

Practice problems

Work each on paper first, then check.

1. Gas expands at a constant 200 kPa from 0.5 to 0.8 m^3 . Work?

$$200 \times 0.3 = 60 \text{ kJ}.$$

2. A shaft delivers $50 \text{ N}\cdot\text{m}$ at 3000 rpm. Power?

$$2\pi \times 50 \times 50 = 15.7 \text{ kW}.$$

3. A 1500 W heater runs 10 minutes. Electrical work?

$$1500 \times 600 = 900 \text{ kJ.}$$

4. Convection: $h = 10 \text{ W}/(\text{m}^2 \cdot \text{K})$, $A = 2 \text{ m}^2$, $\Delta T = 30 \text{ K}$. Heat rate?

600 W.

Common misconceptions

Myth: Work is a property of the state.

Actually: It depends on the path.

Myth: A rigid tank can do boundary work.

Actually: No; $dV = 0$.

Myth: Doubling insulation thickness halves the temperature.

Actually: It halves the conduction heat rate at the same ΔT .

Flashcards

Sign convention

Q in, W out positive.

Boundary work

$\int p \, dV$.

Isothermal

$mRT \ln(V_2/V_1)$.

Polytropic

$(p_2 V_2 - p_1 V_1)/(1 - n)$.

Shaft power

$2\pi \dot{n} T$.

Conduction

$kA\Delta T/L$.

Self-check quiz

1. Boundary work equals...

$\int V \, dp$

$\int p \, dV$

pV

mRT

$\int p \, dV$. Area under p - V curve.

2. Isothermal ideal-gas work is...

$mRT \ln(V_2/V_1)$

$p \, \Delta V$

$mc_v \Delta T$

0

$mRT \ln(V_2/V_1)$. $pV = \text{const.}$

3. Heat and work are...

properties

path functions

always equal

intensive

path functions. Depend on the process.

4. Conduction heat rate is proportional to...

$1/k$

L

$\Delta T/L$

T^4

$\Delta T/L$. $kA\Delta T/L$.

[Try this quiz again](#)

How this helps save the planet

The U.S. Department of Energy explains that concentrating solar-thermal power uses mirrors to concentrate sunlight onto a receiver, heating a high-temperature fluid. That heat spins a turbine or powers an engine to make electricity, and it can also serve industry, from desalination to food processing and chemical production.

DOE notes that utility-scale plants use power towers or rows of linear mirrors, while single dish/engine systems produce 5 to 25 kilowatts each. Every one of them is a heat-transfer and work problem: absorb concentrated radiation, limit conduction and convection losses from the receiver, and turn the heat into shaft work.

On Saving Planets: [Solutions](#) · [Physics II](#)

Sources: U.S. DOE: [Concentrating solar-thermal power basics \(https://www.energy.gov/eere/solar/concentrating-solar-thermal-power-basics\)](https://www.energy.gov/eere/solar/concentrating-solar-thermal-power-basics)

Free learning resources

- [OpenStax UP2, 3.2 Work, heat and internal energy \(https://openstax.org/books/university-physics-volume-2/pages/3-2-work-heat-and-internal-energy\)](https://openstax.org/books/university-physics-volume-2/pages/3-2-work-heat-and-internal-energy): Free textbook section.
- [OpenStax UP2, 1.6 Mechanisms of heat transfer \(https://openstax.org/books/university-physics-volume-2/pages/1-6-mechanisms-of-heat-transfer\)](https://openstax.org/books/university-physics-volume-2/pages/1-6-mechanisms-of-heat-transfer): Free textbook section.
- [MIT OpenCourseWare 16.050 Thermal Energy \(Fall 2002\) \(https://ocw.mit.edu/courses/16-050-thermal-energy-fall-2002/\)](https://ocw.mit.edu/courses/16-050-thermal-energy-fall-2002/): Work and heat lectures.
- [PhET: Energy Forms and Changes \(https://phet.colorado.edu/en/simulations/energy-forms-and-changes\)](https://phet.colorado.edu/en/simulations/energy-forms-and-changes): Energy transfer interactively.



I finished this unit

The First Law for Closed Systems

Energy balance for closed systems, internal energy and enthalpy, specific heats of ideal gases, liquids and solids, constant-volume and constant-pressure heating, latent heat, and energy balances for cycles.

Learning objectives

By the end of this unit you can:

- Write and apply $Q - W = \Delta U + \Delta KE + \Delta PE$.
- Use c_v and c_p for ideal gases, and c for liquids and solids.
- Include latent heat in phase-change problems.
- Show that for a cycle the net heat equals the net work.

Key concepts

- First law for a closed system: $Q - W = \Delta E = \Delta U + \Delta KE + \Delta PE$. Usually ΔKE and ΔPE are negligible, so $Q - W = \Delta U$.
- Enthalpy $h = u + pv$. At constant pressure, the heat added equals the enthalpy change: $Q = m(h_2 - h_1)$, because the boundary work is already included.
- For ideal gases u and h depend only on T : $\Delta u = c_v \Delta T$, $\Delta h = c_p \Delta T$, with $c_p - c_v = R$ and $k = c_p/c_v$ (1.4 for air).
- For liquids and solids $c_p \approx c_v = c$, so $Q = mc\Delta T$. Melting or boiling at constant T needs latent heat: $Q = m h_{if}$ or $m h_{fg}$.
- Over a full cycle the system returns to its starting state, so $\Delta U = 0$ and $Q_{net} = W_{net}$. This is the basis of every engine and refrigerator.

Key equations

$$Q - W = \Delta U + \Delta KE + \Delta PE$$

First law, closed system

$$h = u + pv$$

Enthalpy

$$\Delta u = c_v \Delta T, \Delta h = c_p \Delta T, c_p - c_v = R$$

Ideal-gas specific heats

$$Q = mc\Delta T, \quad Q = m h_{fg}$$

Sensible and latent heat

Worked examples, step by step

Example 4.1 2 kg of air in a rigid tank is heated from 300 K to 400 K. Find Q.

1. $W = 0$ (rigid).
2. $Q = m c_v \Delta T = 2 \times 0.718 \times 100$.

Answer: $Q = 143.6$ kJ.

Example 4.2 The same air is heated at constant pressure (100 kPa) from 300 to 400 K. Find Q and the boundary work.

1. $Q = m c_p \Delta T = 2 \times 1.005 \times 100$.
2. $W = mR\Delta T = 2 \times 0.287 \times 100$.

Answer: $Q = 201.0$ kJ; $W = 57.4$ kJ; $\Delta U = 143.6$ kJ either way.

Example 4.3 Find the heat to warm 1 kg of water from 20 °C to 100 °C, and then to boil 0.1 kg of it away.

1. $Q_1 = 1 \times 4.18 \times 80$.
2. $Q_2 = 0.1 \times 2257$.

Answer: $Q_1 = 334.4$ kJ; $Q_2 = 225.7$ kJ.

Practice problems

Work each on paper first, then check.

1. Melt 0.2 kg of ice at 0 °C. Heat?

$$0.2 \times 334 = 66.8 \text{ kJ.}$$

2. Find $c_p - c_v$ for air.

$$1.005 - 0.718 = 0.287 \text{ kJ/(kg}\cdot\text{K)} = R.$$

3. A cycle receives 500 kJ of heat and rejects 300 kJ. Net work?

200 kJ.

4. Find k for air.

$1.005/0.718 = 1.40$.

Common misconceptions

Myth: Heat added always raises temperature.

Actually: During phase change it does not.

Myth: $Q = mc_p\Delta T$ works for a rigid tank.

Actually: Use c_v when volume is constant.

Myth: Enthalpy is a form of heat.

Actually: It is a property, $u + pv$.

Flashcards

First law

$$Q - W = \Delta U.$$

Enthalpy

$$h = u + pv.$$

Ideal gas Δu

$$c_v\Delta T.$$

Ideal gas Δh

$$c_p\Delta T.$$

Latent heat

$$Q = m h_{fg}.$$

Cycle

$$Q_{\text{net}} = W_{\text{net}}.$$

Self-check quiz

1. For a rigid closed tank, Q equals...

ΔH

ΔU

W

0

ΔU . No boundary work.

2. $c_p - c_v$ for an ideal gas is...

k

R

1

c_v

R. Mayer's relation.

3. Over a cycle, ΔU is...

positive

negative

zero

Q

zero. Same start and end state.

4. At constant pressure, Q equals...

ΔU

ΔH

W

pV

ΔH . $h = u + pv$.

Try this quiz again

How this helps save the planet

DOE reports that heat pumps are growing fast: as of 2020 over 17 million U.S. housing units had them, and they now account for more than half of all residential heating equipment sales in the United States. They work like a refrigerator, using electricity to move heat from a cool space to a warm one rather than making heat.

The first law is why that matters: an electric resistance heater turns each kWh of electricity into exactly one kWh of heat, but a heat pump delivers the electricity plus the heat it pulls from outside. DOE says modern air-source heat pumps can cut electricity use by 50% compared with furnaces and baseboard heaters, and that switching could save up to 7.6 tons of carbon emissions a year depending on the equipment replaced.

On Saving Planets: [Solutions](#) · [Calculus II](#)

Sources: U.S. DOE: [Pump up your savings with heat pumps \(May 30, 2023\)](https://www.energy.gov/articles/pump-your-savings-heat-pumps) (<https://www.energy.gov/articles/pump-your-savings-heat-pumps>)

Free learning resources

- [OpenStax UP2, 3.3 First law of thermodynamics](https://openstax.org/books/university-physics-volume-2/pages/3-3-first-law-of-thermodynamics) (<https://openstax.org/books/university-physics-volume-2/pages/3-3-first-law-of-thermodynamics>): Free textbook section.
- [OpenStax UP2, 3.5 Heat capacities of an ideal gas](https://openstax.org/books/university-physics-volume-2/pages/3-5-heat-capacities-of-an-ideal-gas) (<https://openstax.org/books/university-physics-volume-2/pages/3-5-heat-capacities-of-an-ideal-gas>): Free textbook section.
- [NASA Glenn: First law of thermodynamics](https://www.grc.nasa.gov/www/k-12/airplane/thermo1.html) (<https://www.grc.nasa.gov/www/k-12/airplane/thermo1.html>): Free NASA page.
- [MIT OpenCourseWare 16.01–16.04 Unified Engineering \(2005–2006\)](https://ocw.mit.edu/courses/16-01-unified-engineering-i-ii-iii-iv-fall-2005-spring-2006/) (<https://ocw.mit.edu/courses/16-01-unified-engineering-i-ii-iii-iv-fall-2005-spring-2006/>): First-law notes.



I finished this unit

The First Law for Control Volumes: Steady-Flow Devices

Mass and energy balances for control volumes, flow work and enthalpy, steady-flow devices (nozzles and diffusers, turbines and compressors, pumps, throttling valves, mixing chambers and heat exchangers), and an introduction to unsteady filling.

Learning objectives

By the end of this unit you can:

- Write steady-flow mass and energy balances.
- Explain why enthalpy appears for flowing streams.
- Analyze nozzles, turbines, compressors, throttles and heat exchangers.
- Choose which terms can be neglected for each device.

Key concepts

- Mass balance: in steady flow, $\sum \dot{m}_{in} = \sum \dot{m}_{out}$, with $\dot{m} = \rho AV$.
- Pushing fluid across a boundary takes flow work $p v$ per unit mass; adding it to u gives enthalpy h , which is why open-system balances use h .
- Steady-flow energy equation, one inlet and one outlet: $\dot{Q} - \dot{W} = \dot{m}[(h_2 - h_1) + (V_2^2 - V_1^2)/2 + g(z_2 - z_1)]$.
- Device shortcuts: nozzles trade enthalpy for speed ($\dot{Q} = \dot{W} = 0$); turbines and compressors are near adiabatic with $\dot{W} = \dot{m}(h_1 - h_2)$; throttling valves keep $h_1 = h_2$; heat exchangers have $\dot{W} = 0$ and the heat lost by one stream equals that gained by the other.
- Remember the units: kinetic energy in J/kg must be divided by 1000 to add to kJ/kg enthalpy.

Key equations

$$\sum \dot{m}_{in} = \sum \dot{m}_{out}$$

Steady mass balance

$$\dot{Q} - \dot{W} = \dot{m} \left[\Delta h + \frac{\Delta V^2}{2} + g \Delta z \right]$$

Steady-flow energy equation

$$\dot{W}_{turb} = \dot{m}(h_1 - h_2)$$

Adiabatic turbine

$$h_1 = h_2$$

Worked examples, step by step

Example 5.1 Air enters an adiabatic nozzle slowly at 400 K and leaves at 350 K. Find the exit speed.

$$1. \Delta h = c_p \Delta T = 1.005 \times 50 = 50.25 \text{ kJ/kg} = 50,250 \text{ J/kg.}$$

$$2. V_2 = \sqrt{2 \times 50,250}.$$

Answer: $V_2 = 317.0 \text{ m/s.}$

Example 5.2 Steam flows at 5 kg/s through an adiabatic turbine from $h_1 = 3116.1$ to $h_2 = 2403.0 \text{ kJ/kg.}$ Find the power.

$$1. \dot{W} = 5 \times (3116.1 - 2403.0).$$

Answer: $\dot{W} = 3565.5 \text{ kW} \approx 3.57 \text{ MW.}$

Example 5.3 An adiabatic compressor takes 1.2 kg/s of air from 300 K to 450 K. Find the power input.

$$1. \dot{W}_{\text{in}} = \dot{m} c_p \Delta T = 1.2 \times 1.005 \times 150.$$

Answer: 180.9 kW.

Practice problems

Work each on paper first, then check.

1. Water at 0.5 kg/s is heated from 15 to 45 °C in a heat exchanger. Heat rate?

$$0.5 \times 4.18 \times 30 = 62.7 \text{ kW.}$$

2. Steam is throttled from $h = 2800 \text{ kJ/kg.}$ Exit h ?

$$2800 \text{ kJ/kg.}$$

3. Convert a speed change from 0 to 100 m/s into kJ/kg.

$$100^2/2 = 5000 \text{ J/kg} = 5 \text{ kJ/kg.}$$

4. A pipe has $\dot{m} = 2 \text{ kg/s}$ at inlet. Outlet in steady flow?

2 kg/s.

Common misconceptions

Myth: Turbine power uses u .

Actually: Flowing streams use h , which includes flow work.

Myth: A throttle lowers enthalpy.

Actually: h stays constant; p and usually T drop.

Myth: Kinetic energy is always negligible.

Actually: Not in nozzles and diffusers.

Flashcards

Steady mass

$\dot{m}_{\text{in}} = \dot{m}_{\text{out}}$.

Flow work

pv per kg.

SFEE

$\dot{Q} - \dot{W} = \dot{m}\Delta(h + V^2/2 + gz)$.

Turbine

$\dot{m}(h_1 - h_2)$.

Throttle

$h_1 = h_2$.

Heat exchanger

Heat lost = heat gained.

Self-check quiz

1. For a throttling valve...

$$h_1 = h_2$$

$$T_1 = T_2$$

$$p_1 = p_2$$

$$W > 0$$

$h_1 = h_2$. No work, no heat, small ΔKE .

2. Enthalpy appears in open systems because of...

flow work

friction

gravity

radiation

flow work. $h = u + pv$.

3. A nozzle converts...

speed into enthalpy

enthalpy into speed

work into heat

mass into energy

enthalpy into speed. Accelerates flow.

4. Adiabatic turbine power is...

$\dot{m}(h_1 - h_2)$

$\dot{m}(h_2 - h_1)$

$\dot{Q}$

0

$\dot{m}(h_1 - h_2)$. Enthalpy drop.

Try this quiz again

How this helps save the planet

DOE describes the core of a nuclear plant as a chain of steady-flow devices: fission heats water, a heat exchanger (in pressurized-water reactors) makes steam in a separate loop, the steam spins a

turbine connected to a generator, and leftover steam is condensed back to water and pumped back to be reheated.

Each box is one steady-flow energy equation. Geothermal plants, which DOE says draw hot fluid up through wells and convert its heat to steam that drives turbines, use the same devices with Earth's heat as the source. Getting a few more kJ per kg out of every turbine stage is how plant efficiency climbs.

On Saving Planets: [Solutions](#) · [Aerodynamics I](#)

Sources: [U.S. DOE: Nuclear 101: How does a nuclear reactor work? \(May 2025\)](#) (<https://www.energy.gov/ne/articles/nuclear-101-how-does-nuclear-reactor-work>) · [U.S. DOE: Geothermal basics](#) (<https://www.energy.gov/eere/geothermal/geothermal-basics>)

Free learning resources

- [OpenStax UP2, 3.4 Thermodynamic processes](https://openstax.org/books/university-physics-volume-2/pages/3-4-thermodynamic-processes) (<https://openstax.org/books/university-physics-volume-2/pages/3-4-thermodynamic-processes>): Free textbook section.
- [MIT OpenCourseWare 16.050 Thermal Energy \(Fall 2002\)](https://ocw.mit.edu/courses/16-050-thermal-energy-fall-2002/) (<https://ocw.mit.edu/courses/16-050-thermal-energy-fall-2002/>): Control-volume lectures.
- [NIST Chemistry WebBook: Thermophysical properties of fluid systems](https://webbook.nist.gov/chemistry/fluid/) (<https://webbook.nist.gov/chemistry/fluid/>): Steam data.
- [MIT OpenCourseWare 16.01–16.04 Unified Engineering \(2005–2006\)](https://ocw.mit.edu/courses/16-01-unified-engineering-i-ii-iii-iv-fall-2005-spring-2006/) (<https://ocw.mit.edu/courses/16-01-unified-engineering-i-ii-iii-iv-fall-2005-spring-2006/>): Steady-flow notes.



I finished this unit

The Second Law: Heat Engines, Refrigerators and Carnot Limits

Thermal reservoirs, heat engines and thermal efficiency, refrigerators, heat pumps and COP, the Kelvin–Planck and Clausius statements, reversible and irreversible processes, the Carnot cycle, and the Carnot limits on efficiency and COP.

Learning objectives

By the end of this unit you can:

- Compute thermal efficiency and COP.
- State the Kelvin–Planck and Clausius statements.
- Identify sources of irreversibility.
- Use Carnot limits to judge whether a claimed device is possible.

Key concepts

- A heat engine takes Q_H from a hot reservoir, rejects Q_L to a cold one, and produces $W = Q_H - Q_L$. Thermal efficiency $\eta = W/Q_H = 1 - Q_L/Q_H$.
- Kelvin–Planck: no cycle can turn all the heat from a single reservoir into work, so $\eta < 100\%$. Clausius: heat does not flow from cold to hot by itself; a refrigerator or heat pump needs work input.
- $COP_R = Q_L/W$ for a refrigerator; $COP_{HP} = Q_H/W = COP_R + 1$ for a heat pump. COP can be well above 1, which is why heat pumps beat resistance heaters.
- Irreversibilities (friction, heat transfer across a finite ΔT , unrestrained expansion, mixing) reduce performance. A reversible cycle between two reservoirs, the Carnot cycle, is the best possible.
- Carnot limits use absolute temperatures: $\eta_{Carnot} = 1 - T_L/T_H$, $COP_{R,Carnot} = T_L/(T_H - T_L)$, $COP_{HP,Carnot} = T_H/(T_H - T_L)$.

Key equations

$$\eta = \frac{W}{Q_H} = 1 - \frac{Q_L}{Q_H}$$

Thermal efficiency

$$COP_R = \frac{Q_L}{W}, \quad COP_{HP} = \frac{Q_H}{W}$$

Coefficients of performance

$$\eta_{Carnot} = 1 - \frac{T_L}{T_H}$$

Carnot efficiency

$$COP_{HP,Carnot} = \frac{T_H}{T_H - T_L}$$

Carnot heat pump

Worked examples, step by step

Example 6.1 An engine takes 1000 kJ of heat and produces 350 kJ of work. Find η and Q_L .

1. $\eta = 350/1000$.
2. $Q_L = 1000 - 350$.

Answer: $\eta = 35\%$; $Q_L = 650$ kJ.

Example 6.2 Find the Carnot efficiency between 800 K and 300 K, and between 1073 K and 293 K.

1. $1 - 300/800$.
2. $1 - 293/1073$.

Answer: 62.5% and 72.7%.

Example 6.3 A heat pump keeps a house at 294 K when it is 273 K outside. Find the Carnot COP, and the heat delivered by a real unit with $COP = 3$ (sample value) using 3 kWh.

1. $COP = 294/(294 - 273)$.
2. $Q_H = 3 \times 3$.

Answer: $COP_{Carnot} = 14.0$; the real unit delivers 9 kWh of heat.

Practice problems

Work each on paper first, then check.

1. A fridge has $COP_R = 2.5$ and removes 500 kJ. Work?

200 kJ.

2. Find COP_{HP} if $COP_R = 2.5$.

3.5.

3. A fridge works between 275 K and 298 K. Carnot COP_R?

$$275/23 = 11.96.$$

4. An inventor claims 70% efficiency between 600 K and 300 K. Possible?

No: Carnot limit is 50%.

Common misconceptions

Myth: COP above 1 breaks energy conservation.

Actually: The heat pump moves heat; it does not create it.

Myth: Carnot efficiency can use °C.

Actually: It must use kelvin.

Myth: Better engineering can reach 100% efficiency.

Actually: Kelvin–Planck forbids it.

Flashcards

Efficiency

$$W/Q_H.$$

COP_R

$$Q_L/W.$$

COP_{HP}

$$Q_H/W.$$

Kelvin–Planck

No 100% engine.

Clausius

No cold-to-hot without work.

Carnot

$$1 - T_L/T_H.$$

Self-check quiz

1. Carnot efficiency between 600 K and 300 K is... _____

25%

50%

75%

100%

50%. 1 – 0.5.

2. COP_HP – COP_R equals...

0

1

η

T_H

1. $Q_H = Q_L + W$.

3. Which statement forbids a 100% efficient engine?

Clausius

Kelvin–Planck

Zeroth law

First law

Kelvin–Planck. Single-reservoir statement.

4. Which is an irreversibility?

friction

quasi-equilibrium compression

isentropic expansion

none

friction. Dissipation.

Try this quiz again

How this helps save the planet

DOE describes heat pumps as moving heat rather than generating it, which makes them significantly more efficient than traditional heating. Modern air-source heat pumps can cut electricity use by 50% compared with furnaces and baseboard heaters, and geothermal heat pumps, which use the steady temperature of the shallow ground, can reduce energy use by 30% to 60%.

The Carnot COP explains both claims: the smaller the temperature lift $T_H - T_L$, the higher the COP. The ground stays milder than winter air, so a ground-source heat pump lifts heat across a smaller gap. DOE's geothermal office sees potential for up to 28 million geothermal heat pumps by 2050.

On Saving Planets: [Solutions](#) · [Oceans](#)

Sources: [U.S. DOE: Pump up your savings with heat pumps \(May 30, 2023\)](#) (<https://www.energy.gov/articles/pump-your-savings-heat-pumps>) · [U.S. DOE: Geothermal basics](#) (<https://www.energy.gov/eere/geothermal/geothermal-basics>)

Free learning resources

- [OpenStax UP2, 4.2 Heat engines](https://openstax.org/books/university-physics-volume-2/pages/4-2-heat-engines) (<https://openstax.org/books/university-physics-volume-2/pages/4-2-heat-engines>): Free textbook section.
- [OpenStax UP2, 4.3 Refrigerators and heat pumps](https://openstax.org/books/university-physics-volume-2/pages/4-3-refrigerators-and-heat-pumps) (<https://openstax.org/books/university-physics-volume-2/pages/4-3-refrigerators-and-heat-pumps>): Free textbook section.
- [OpenStax UP2, 4.5 The Carnot cycle](https://openstax.org/books/university-physics-volume-2/pages/4-5-the-carnot-cycle) (<https://openstax.org/books/university-physics-volume-2/pages/4-5-the-carnot-cycle>): Free textbook section.
- [NASA Glenn: Carnot cycle](https://www.grc.nasa.gov/www/k-12/airplane/carnot.html) (<https://www.grc.nasa.gov/www/k-12/airplane/carnot.html>): Free NASA page.



I finished this unit

Entropy and Isentropic Efficiency

The Clausius inequality, entropy as a property, the increase-of-entropy principle and entropy generation, the $T ds$ relations, entropy change of liquids, solids and ideal gases, isentropic processes, T - s diagrams, and isentropic efficiencies of turbines, compressors and nozzles.

Learning objectives

By the end of this unit you can:

- Compute entropy changes for liquids, solids and ideal gases.
- Find entropy generation and decide if a process is possible.
- Use isentropic relations for ideal gases.
- Apply isentropic efficiencies to real devices.

Key concepts

- Entropy S is a property defined by $dS = \delta Q_{rev}/T$. For any process, $S_2 - S_1 \geq \int \delta Q/T$; the difference is the entropy generated, $S_{gen} \geq 0$ (zero only if reversible).
- Increase-of-entropy principle: the entropy of an isolated system (system plus surroundings) never decreases. A process with $S_{gen} < 0$ is impossible.
- $T ds$ relations: $T ds = du + p dv = dh - v dp$. For liquids and solids $\Delta s = c \ln(T_2/T_1)$; for ideal gases $\Delta s = c_p \ln(T_2/T_1) - R \ln(p_2/p_1)$.
- An isentropic (reversible adiabatic) ideal-gas process with constant specific heats has $T_2/T_1 = (p_2/p_1)^{((k-1)/k)}$. On a T - s diagram it is a vertical line, and the area under a reversible process is the heat transferred.
- Real devices are compared with isentropic ones: $\eta_T = (h_1 - h_{2a})/(h_1 - h_{2s})$ for turbines and $\eta_C = (h_{2s} - h_1)/(h_{2a} - h_1)$ for compressors.

Key equations

$$dS = \frac{\delta Q_{rev}}{T}, \quad S_{gen} \geq 0$$

Entropy and the second law

$$\Delta s = c \ln \frac{T_2}{T_1}$$

Liquids and solids

$$\Delta s = c_p \ln \frac{T_2}{T_1} - R \ln \frac{p_2}{p_1}$$

Ideal gas

$$\frac{T_2}{T_1} = \left(\frac{p_2}{p_1} \right)^{(k-1)/k}$$

Isentropic ideal gas

Worked examples, step by step

Example 7.1 Find the entropy change of 2 kg of water heated from 293 K to 353 K.

1. $\Delta S = 2 \times 4.18 \times \ln(353/293)$.

Answer: $\Delta S = 1.557 \text{ kJ/K}$.

Example 7.2 Air goes from 300 K and 100 kPa to 500 K and 400 kPa. Find Δs .

1. $\Delta s = 1.005 \ln(500/300) - 0.287 \ln(400/100)$.

Answer: $\Delta s = 0.1155 \text{ kJ/(kg}\cdot\text{K)}$.

Example 7.3 Air at 300 K is compressed through a pressure ratio of 8. Find the isentropic exit temperature and the actual one if $\eta_C = 0.85$.

1. $T_{2s} = 300 \times 8^{(0.4/1.4)} = 543.4 \text{ K}$.

2. $T_{2a} = 300 + (543.4 - 300)/0.85$.

Answer: $T_{2s} = 543.4 \text{ K}$; $T_{2a} = 586.4 \text{ K}$.

Practice problems

Work each on paper first, then check.

1. 1000 kJ of heat flows from an 800 K reservoir to a 300 K one. S_{gen} ?

$1000/300 - 1000/800 = 2.083 \text{ kJ/K}$.

2. Isentropic T_2 for a pressure ratio of 10 from 300 K?

579.2 K.

3. Can S_{gen} be negative?

No; that process is impossible.

4. What does area under a reversible T-s curve represent?

Heat transferred.

Common misconceptions

Myth: Entropy can never decrease.

Actually: A system's entropy can fall if it rejects heat; the total for an isolated system cannot.

Myth: Adiabatic means isentropic.

Actually: Only if also reversible.

Myth: Isentropic efficiency can exceed 1.

Actually: Not for turbines or compressors.

Flashcards

Entropy

$$dS = \delta Q_{\text{rev}}/T.$$

S_gen

$$\geq 0.$$

Liquid Δs

$$c \ln(T_2/T_1).$$

Ideal gas Δs

$$c_p \ln(T_2/T_1) - R \ln(p_2/p_1).$$

Isentropic T

$$T_2/T_1 = (p_2/p_1)^{((k-1)/k)}.$$

η_T

$$(h_1 - h_{2a})/(h_1 - h_{2s}).$$

Self-check quiz

1. S_gen for a reversible process is...

positive

zero

negative

infinite

zero. No irreversibility.

2. An isentropic process on a T-s diagram is...

horizontal

vertical

diagonal

circular

vertical. s constant.

3. Δs for a liquid heated is...

$c \ln(T_2/T_1)$

$c\Delta T$

$R \ln(p_2/p_1)$

0

$c \ln(T_2/T_1)$. Incompressible.

4. Compressor isentropic efficiency is...

$(h_2s - h_1)/(h_2a - h_1)$

$(h_2a - h_1)/(h_2s - h_1)$

h_2/h_1

1

$(h_2s - h_1)/(h_2a - h_1)$. Ideal work over actual.

Try this quiz again

How this helps save the planet

NASA Glenn's Brayton-cycle page walks through a gas turbine on a T-s diagram: ideally the compressor raises pressure and temperature isentropically, a vertical line, but in reality the compression line leans to the right because entropy increases in the flow. Combustion happens at constant pressure, and the turbine, on the same shaft, drives the compressor.

NASA notes that the area enclosed on the T-s diagram is proportional to the useful work. Every bit of entropy generated in a compressor or turbine shrinks that area, so higher isentropic efficiencies mean more electricity or thrust from the same fuel, and less CO₂.

On Saving Planets: [Aerodynamics I](#) · [Calculus III](#)

Sources: [NASA Glenn: Turbine engine thermodynamic cycle \(Brayton cycle\)](https://www.grc.nasa.gov/www/k-12/airplane/brayton.html) (<https://www.grc.nasa.gov/www/k-12/airplane/brayton.html>)

Free learning resources

- [OpenStax UP2, 4.6 Entropy](https://openstax.org/books/university-physics-volume-2/pages/4-6-entropy) (<https://openstax.org/books/university-physics-volume-2/pages/4-6-entropy>): Free textbook section.
- [OpenStax UP2, 4.7 Entropy on a microscopic scale](https://openstax.org/books/university-physics-volume-2/pages/4-7-entropy-on-a-microscopic-scale) (<https://openstax.org/books/university-physics-volume-2/pages/4-7-entropy-on-a-microscopic-scale>): Free textbook section.
- [NASA Glenn: Entropy](https://www.grc.nasa.gov/www/k-12/airplane/entropy.html) (<https://www.grc.nasa.gov/www/k-12/airplane/entropy.html>): Free NASA page.
- [OpenStax UP2, 3.6 Adiabatic processes for an ideal gas](https://openstax.org/books/university-physics-volume-2/pages/3-6-adiabatic-processes-for-an-ideal-gas) (<https://openstax.org/books/university-physics-volume-2/pages/3-6-adiabatic-processes-for-an-ideal-gas>): Free textbook section.



I finished this unit

Exergy: How Much Energy Is Useful

Dead state and surroundings, exergy (availability) of heat and of flowing streams, reversible work and irreversibility, exergy destruction $I = T_0 S_{\text{gen}}$, second-law efficiency, and why matching energy quality to use matters.

Learning objectives

By the end of this unit you can:

- Compute the exergy of heat from a reservoir.
- Relate exergy destroyed to entropy generated.
- Compute second-law efficiency.
- Explain why combined heat and power and heat pumps use exergy well.

Key concepts

- Exergy is the maximum useful work obtainable as a system comes to equilibrium with its surroundings (the dead state, T_0 and p_0). Energy is conserved; exergy is destroyed by irreversibility.
- Heat Q from a reservoir at T has exergy $X = Q(1 - T_0/T)$: heat at high temperature is valuable, heat near room temperature is almost worthless for work.
- Exergy of a flowing stream per unit mass: $\psi = (h - h_0) - T_0(s - s_0) + V^2/2 + gz$.
- Exergy destroyed (irreversibility) $I = T_0 S_{\text{gen}}$ (Gouy–Stodola). Every irreversibility costs useful work.
- Second-law efficiency $\eta_{\text{II}} = \eta_{\text{th}}/\eta_{\text{rev}}$ for engines, or $\text{COP}/\text{COP}_{\text{rev}}$ for heat pumps. Burning fuel at 2000 K just to heat water to 60 °C wastes most of the exergy; using the waste heat of a power plant for that job does not.

Key equations

$$X_Q = Q \left(1 - \frac{T_0}{T} \right)$$

Exergy of heat

$$\psi = (h - h_0) - T_0(s - s_0) + \frac{V^2}{2} + gz$$

Flow exergy

$$I = T_0 S_{\text{gen}}$$

Exergy destroyed

$$\eta_{II} = \frac{\eta_{th}}{\eta_{rev}}$$

Second-law efficiency

Worked examples, step by step

Example 8.1 Find the exergy of 100 kJ of heat from a 600 K source with $T_0 = 300$ K.

$$1. X = 100 \times (1 - 300/600).$$

Answer: 50 kJ.

Example 8.2 1000 kJ flows from 800 K to 300 K ($T_0 = 300$ K). Find the exergy destroyed.

$$1. S_{gen} = 1000/300 - 1000/800 = 2.083 \text{ kJ/K.}$$

$$2. I = 300 \times 2.083.$$

Answer: $I = 625$ kJ, all the exergy the heat had at 800 K.

Example 8.3 An engine with $\eta = 35\%$ runs between 800 K and 300 K. Find η_{II} .

$$1. \eta_{rev} = 62.5\%.$$

$$2. \eta_{II} = 0.35/0.625.$$

Answer: $\eta_{II} = 56\%$.

Practice problems

Work each on paper first, then check.

1. Exergy of 100 kJ at 330 K with $T_0 = 300$ K?

$$100 \times (1 - 300/330) = 9.09 \text{ kJ.}$$

2. A heat pump has COP 3; $COP_{rev} = 14$. η_{II} ?

$$3/14 = 21.4\%.$$

3. Why is room-temperature heat nearly worthless for work?

Its exergy factor $1 - T_0/T$ is near zero.

4. What destroys exergy?

Every irreversibility: friction, mixing, heat transfer across finite ΔT .

Common misconceptions

Myth: Energy and exergy are the same.

Actually: Energy is conserved; exergy is destroyed.

Myth: High first-law efficiency means a good process.

Actually: A 95% efficient gas boiler can have a low second-law efficiency.

Myth: Exergy depends only on the system.

Actually: It depends on the surroundings (T_0 , p_0) too.

Flashcards

Exergy

Maximum useful work.

Heat exergy

$Q(1 - T_0/T)$.

Dead state

T_0 , p_0 .

Irreversibility

$I = T_0 S_{\text{gen}}$.

η_{II}

η/η_{rev} .

Energy quality

High T is valuable.

Self-check quiz

1. Exergy destroyed equals...

$T_0 S_{\text{gen}}$

Q

W

ΔU

$T_0 S_{\text{gen}}$. Gouy–Stodola.

2. Exergy of heat at $T = T_0$ is...

Q

zero

infinite

$Q/2$

zero. $1 - T_0/T = 0$.

3. η_{II} compares actual performance with...

the reversible limit

zero

100%

the first law

the reversible limit. Second-law efficiency.

4. The dead state is...

equilibrium with surroundings

absolute zero

the critical point

vacuum

equilibrium with surroundings. T_0, p_0 .

Try this quiz again

How this helps save the planet

DOE explains that combined heat and power (cogeneration) produces electricity and useful heating or cooling from a single fuel at or near where it is used, recovering heat that would otherwise be lost in power generation. DOE says CHP can reasonably operate at 65% to 75% efficiency, versus a national average of about 50% when electricity and heat are produced separately.

Exergy explains the win: the high-temperature part of the fuel's exergy makes electricity, and the low-grade heat that a power plant would throw away meets heating needs that only ever required low-exergy energy. Going from 50% to 75% means the same services from two-thirds of the fuel.

On Saving Planets: [Solutions](#) · [Space Weather](#)

Sources: U.S. DOE: Combined heat and power basics (<https://www.energy.gov/eere/amo/combined-heat-and-power-basics>)

Free learning resources

- [MIT OpenCourseWare 16.050 Thermal Energy \(Fall 2002\)](https://ocw.mit.edu/courses/16-050-thermal-energy-fall-2002/) (<https://ocw.mit.edu/courses/16-050-thermal-energy-fall-2002/>): Availability lectures.
- [OpenStax UP2, 4.1 Reversible and irreversible processes](https://openstax.org/books/university-physics-volume-2/pages/4-1-reversible-and-irreversible-processes) (<https://openstax.org/books/university-physics-volume-2/pages/4-1-reversible-and-irreversible-processes>): Free textbook section.
- [OpenStax UP2, 4.4 Statements of the second law](https://openstax.org/books/university-physics-volume-2/pages/4-4-statements-of-the-second-law-of-thermodynamics) (<https://openstax.org/books/university-physics-volume-2/pages/4-4-statements-of-the-second-law-of-thermodynamics>): Free textbook section.
- [MIT OpenCourseWare 16.01–16.04 Unified Engineering \(2005–2006\)](https://ocw.mit.edu/courses/16-01-unified-engineering-i-ii-iii-iv-fall-2005-spring-2006/) (<https://ocw.mit.edu/courses/16-01-unified-engineering-i-ii-iii-iv-fall-2005-spring-2006/>): Second-law notes.



I finished this unit

Gas Power Cycles: Otto, Diesel and Brayton

Air-standard assumptions, mean effective pressure, the Otto cycle (spark ignition), the Diesel cycle (compression ignition), the Brayton cycle for gas turbines and jet engines, back-work ratio, regeneration, intercooling and reheat, and combined cycles.

Learning objectives

By the end of this unit you can:

- Analyze ideal Otto and Diesel cycles.
- Analyze the ideal Brayton cycle, including back-work ratio.
- Explain how compression ratio and pressure ratio raise efficiency.
- Describe regeneration and combined cycles.

Key concepts

- Air-standard assumptions: the working fluid is air, an ideal gas, in a closed cycle; combustion is replaced by heat addition and exhaust by heat rejection. Cold-air-standard adds constant specific heats at room temperature.
- Otto cycle: isentropic compression, constant-volume heat addition, isentropic expansion, constant-volume heat rejection. $\eta_{\text{Otto}} = 1 - 1/r^{k-1}$, with compression ratio $r = V_{\text{max}}/V_{\text{min}}$.
- Diesel cycle: heat is added at constant pressure; with cutoff ratio r_c , $\eta_{\text{Diesel}} = 1 - (1/r^{k-1}) \cdot (r_c^k - 1)/(k(r_c - 1))$. Diesels run at higher r , so they are more efficient in practice.
- Brayton cycle (gas turbines): isentropic compression, constant-pressure heat addition, isentropic expansion, constant-pressure heat rejection. $\eta_{\text{Brayton}} = 1 - 1/r_p^{(k-1)/k}$. A large share of turbine work drives the compressor (the back-work ratio).
- Regeneration uses hot exhaust to preheat compressed air; intercooling and reheat move the cycle toward Carnot. A combined cycle feeds gas-turbine exhaust to a steam (Rankine) cycle.

Key equations

$$\eta_{\text{Otto}} = 1 - \frac{1}{r^{k-1}}$$

Otto cycle

$$\eta_{\text{Diesel}} = 1 - \frac{1}{r^{k-1}} \frac{r_c^k - 1}{k(r_c - 1)}$$

Diesel cycle

$$\eta_{Brayton} = 1 - \frac{1}{r_p^{(k-1)/k}}$$

Brayton cycle

$$r_{bw} = \frac{w_{comp}}{w_{turb}}$$

Back-work ratio

Worked examples, step by step

Example 9.1 Find the cold-air-standard efficiency of Otto cycles with $r = 8$ and $r = 10$.

$$1. 1 - 8^{-0.4}.$$

$$2. 1 - 10^{-0.4}.$$

Answer: 56.5% and 60.2%.

Example 9.2 A Diesel cycle has $r = 18$ and $r_c = 2$. Find η .

$$1. 1/r^{0.4} = 0.3147.$$

$$2. (2^{1.4} - 1)/(1.4 \times 1) = 1.1703.$$

$$3. \eta = 1 - 0.3147 \times 1.1703.$$

Answer: $\eta = 63.2\%$.

Example 9.3 An ideal Brayton cycle has $r_p = 8$, inlet 300 K and turbine inlet 1300 K. Find T_2 , T_4 , compressor and turbine work, back-work ratio, net work and η .

$$1. T_2 = 300 \times 8^{0.2857} = 543.4 \text{ K}; T_4 = 1300/1.8114 = 717.7 \text{ K}.$$

$$2. w_c = 1.005 \times 243.4 = 244.7 \text{ kJ/kg}; w_t = 1.005 \times 582.3 = 585.3 \text{ kJ/kg}.$$

$$3. r_{bw} = 244.7/585.3; w_{net} = 340.6 \text{ kJ/kg}; \eta = 1 - 8^{-0.2857}.$$

Answer: $r_{bw} = 0.418$, $w_{net} = 340.6 \text{ kJ/kg}$, $\eta = 44.8\%$.

Practice problems

Work each on paper first, then check.

1. Brayton efficiency at $r_p = 12$?

$$1 - 12^{(-0.2857)} = 50.8\%.$$

2. Why are Diesel engines more efficient than gasoline ones in practice?

They run at much higher compression ratios.

3. Raising r in an Otto cycle from 8 to 10 adds how many points?

$$60.2 - 56.5 = 3.7 \text{ points.}$$

4. What does regeneration do?

Uses exhaust heat to preheat compressor air, cutting fuel needed.

Common misconceptions

Myth: Higher compression always means more efficient real engines.

Actually: Knock limits spark-ignition engines.

Myth: Back work is negligible in gas turbines.

Actually: Often 40–80% of turbine work.

Myth: Air-standard efficiency is the real efficiency.

Actually: Real engines are much lower due to friction, heat loss and real gases.

Flashcards

Air standard

Air, ideal gas, closed cycle.

Otto

$$1 - 1/r^{(k-1)}.$$

Diesel

Constant- p heat addition.

Brayton

$$1 - 1/r_p^{((k-1)/k)}.$$

Back work

$$w_c/w_t.$$

Regeneration

Exhaust preheats air.

Self-check quiz

1. Otto efficiency depends on...

compression ratio

fuel type only

speed

cutoff ratio

compression ratio. $1 - 1/r^{(k-1)}$.

2. Brayton heat addition is at constant...

volume

pressure

temperature

entropy

pressure. Combustor.

3. Back-work ratio is...

w_c/w_t

w_t/w_c

η

r_p

w_c/w_t . Compressor over turbine.

4. A combined cycle pairs Brayton with...

Otto

Rankine

Diesel

Carnot

Rankine. Steam bottoming cycle.

Try this quiz again

How this helps save the planet

NASA Glenn explains that the Brayton cycle is used in all gas turbine engines, whether turbojets, turbofans or turboprops, and that all share a compressor, a combustion section and a turbine that drives the compressor. NASA's EngineSim program uses Brayton-cycle analysis to predict an engine's thrust and fuel flow.

Ground-based gas turbines run the same cycle. EIA's heat-rate examples show why cycle design matters: 7,500 Btu/kWh is about 45% efficient versus about 33% at 10,500 Btu/kWh. Raising pressure ratio and turbine temperature, and recovering exhaust heat, are how plants move toward the better number.

On Saving Planets: [Aerodynamics I](#) · [Intro to Aerospace Engineering](#)

Sources: [NASA Glenn: Turbine engine thermodynamic cycle \(Brayton cycle\)](https://www.grc.nasa.gov/www/k-12/airplane/brayton.html) (<https://www.grc.nasa.gov/www/k-12/airplane/brayton.html>) · [U.S. EIA: What is the efficiency of different types of power plants?](https://www.eia.gov/tools/faqs/faq.php?id=107&t=3) (<https://www.eia.gov/tools/faqs/faq.php?id=107&t=3>)

Free learning resources

- [NASA Glenn: Brayton cycle](https://www.grc.nasa.gov/www/k-12/airplane/brayton.html) (<https://www.grc.nasa.gov/www/k-12/airplane/brayton.html>): Free NASA page.
- [NASA Glenn: Otto cycle](https://www.grc.nasa.gov/www/k-12/airplane/otto.html) (<https://www.grc.nasa.gov/www/k-12/airplane/otto.html>): Free NASA page.
- [MIT OpenCourseWare 16.050 Thermal Energy \(Fall 2002\)](https://ocw.mit.edu/courses/16-050-thermal-energy-fall-2002/) (<https://ocw.mit.edu/courses/16-050-thermal-energy-fall-2002/>): Cycle lectures.
- [MIT OpenCourseWare 16.01–16.04 Unified Engineering \(2005–2006\)](https://ocw.mit.edu/courses/16-01-unified-engineering-i-ii-iii-iv-fall-2005-spring-2006/) (<https://ocw.mit.edu/courses/16-01-unified-engineering-i-ii-iii-iv-fall-2005-spring-2006/>): Propulsion cycle notes.



I finished this unit

Vapor Power and Refrigeration Cycles

The ideal Rankine cycle and its four devices, pump work, raising efficiency (higher boiler pressure and temperature, lower condenser pressure, reheat, regeneration), the vapor-compression refrigeration cycle and heat pumps, refrigerants, and cogeneration.

Learning objectives

By the end of this unit you can:

- Analyze an ideal Rankine cycle with steam tables.
- Explain how pressure, superheat and reheat change efficiency.
- Analyze an ideal vapor-compression refrigeration cycle.
- Relate cycle COP to heat pump performance.

Key concepts

- Ideal Rankine cycle: pump (isentropic compression of liquid), boiler (constant-pressure heating to superheated steam), turbine (isentropic expansion), condenser (constant-pressure condensation).
- Pump work is small because liquid has small v : $w_p \approx v(p_2 - p_1)$. Net work = $w_{\text{turb}} - w_{\text{pump}}$; $\eta = w_{\text{net}}/q_{\text{in}}$.
- Efficiency rises with higher average heat-addition temperature (higher boiler pressure, more superheat, reheat) and lower condenser pressure. Regeneration with feedwater heaters preheats the water using steam bled from the turbine.
- Vapor-compression refrigeration: compressor (to superheated vapor), condenser (rejects Q_H), expansion valve (throttle, $h_3 = h_4$), evaporator (absorbs Q_L). $\text{COP}_R = (h_1 - h_4)/(h_2 - h_1)$.
- A heat pump is the same cycle used for heating, with $\text{COP}_{\text{HP}} = (h_2 - h_3)/(h_2 - h_1)$. Refrigerants are chosen for their saturation properties, safety and low global-warming potential.

Key equations

$$w_p = v(p_2 - p_1)$$

Pump work

$$\eta = \frac{w_t - w_p}{q_{\text{in}}}$$

Rankine efficiency

$$\text{COP}_R = \frac{h_1 - h_4}{h_2 - h_1}$$

Refrigerator COP

$$h_3 = h_4$$

Expansion valve

Worked examples, step by step

Example 10.1 An ideal Rankine cycle runs between 3 MPa/350 °C and 75 kPa. Steam tables: $h_1 = 384.44$, $v_1 = 0.001037 \text{ m}^3/\text{kg}$, $h_3 = 3116.1$, $h_4 = 2403.0 \text{ kJ/kg}$. Find w_p , q_{in} , w_{net} and η .

1. $w_p = 0.001037 \times (3000 - 75) = 3.03 \text{ kJ/kg}$; $h_2 = 387.47$.
2. $q_{in} = 3116.1 - 387.47 = 2728.6 \text{ kJ/kg}$.
3. $w_{net} = (3116.1 - 2403.0) - 3.03 = 710.1 \text{ kJ/kg}$; $\eta = 710.1/2728.6$.

Answer: $w_p = 3.03 \text{ kJ/kg}$, $q_{in} = 2728.6 \text{ kJ/kg}$, $w_{net} = 710.1 \text{ kJ/kg}$, $\eta = 26.0\%$.

Example 10.2 A vapor-compression cycle has $h_1 = 244.5$, $h_2 = 275.4$ and $h_3 = h_4 = 95.5 \text{ kJ/kg}$ (sample values). Find q_L , w_{in} and COP_R .

1. $q_L = 244.5 - 95.5 = 149.0 \text{ kJ/kg}$.
2. $w = 275.4 - 244.5 = 30.9 \text{ kJ/kg}$.
3. $COP = 149.0/30.9$.

Answer: $q_L = 149.0 \text{ kJ/kg}$, $w = 30.9 \text{ kJ/kg}$, $COP_R = 4.82$.

Example 10.3 For that cycle used as a heat pump, find COP_{HP} .

1. $q_H = 275.4 - 95.5 = 179.9 \text{ kJ/kg}$.
2. $COP_{HP} = 179.9/30.9$.

Answer: $COP_{HP} = 5.82 (= COP_R + 1)$.

Practice problems

Work each on paper first, then check.

1. In the Rankine example, what is the heat rejected?

$$2403.0 - 384.44 = 2018.6 \text{ kJ/kg}.$$

2. What fraction of turbine work does the pump use?

$$3.03/713.1 = 0.425\%.$$

3. Find the steam flow for 100 MW net in the example.

$$100,000/710.1 = 140.8 \text{ kg/s.}$$

4. Why does lowering condenser pressure help?

It lowers the heat-rejection temperature.

Common misconceptions

Myth: Pump work in a Rankine cycle is large.

Actually: It is tiny because liquid is nearly incompressible.

Myth: The expansion valve does work.

Actually: It is a throttle: h constant, no work.

Myth: More superheat always helps with no limit.

Actually: Turbine materials limit temperature.

Flashcards

Rankine

Pump, boiler, turbine, condenser.

Pump work

$$v(p_2 - p_1).$$

Reheat

Raises mean heat-addition T , drier exhaust.

Vapor compression

Compressor, condenser, valve, evaporator.

COP_R

$$(h_1 - h_4)/(h_2 - h_1).$$

Throttle

$$h_3 = h_4.$$

Self-check quiz

1. In a Rankine cycle, heat is added in the...

pump

boiler

turbine

condenser

boiler. Constant pressure.

2. Pump work is about...

$v \Delta p$

$c_p \Delta T$

h_{fg}

zero exactly

$v \Delta p$. Incompressible liquid.

3. In refrigeration, Q_L is absorbed in the...

condenser

evaporator

compressor

valve

evaporator. Cold side.

4. COP_{HP} minus COP_R is...

0

1

η

2

1. $q_H = q_L + w$.

Try this quiz again

How this helps save the planet

DOE's geothermal office explains that geothermal plants bring hot fluid up through wells and convert its heat to steam that drives turbines, a Rankine-family cycle with Earth as the boiler. Geothermal plants can run essentially 24 hours a day regardless of weather, and DOE's analysis sees potential for 90 gigawatts of U.S. geothermal electricity by 2050 if enhanced geothermal costs fall.

Nuclear plants use the same Rankine cycle, and DOE's heat pump article describes the vapor-compression cycle in reverse: moving heat into homes in winter and out in summer. Better Rankine and refrigeration cycles are where much of the world's clean electricity and efficient heating will come from.

On Saving Planets: [Solutions](#) · [Earth Observation](#)

Sources: [U.S. DOE: Geothermal basics \(https://www.energy.gov/eere/geothermal/geothermal-basics\)](https://www.energy.gov/eere/geothermal/geothermal-basics) · [U.S. DOE: Nuclear 101: How does a nuclear reactor work? \(May 2025\) \(https://www.energy.gov/ne/articles/nuclear-101-how-does-nuclear-reactor-work\)](https://www.energy.gov/ne/articles/nuclear-101-how-does-nuclear-reactor-work) · [U.S. DOE: Pump up your savings with heat pumps \(May 30, 2023\) \(https://www.energy.gov/articles/pump-your-savings-heat-pumps\)](https://www.energy.gov/articles/pump-your-savings-heat-pumps)

Free learning resources

- [NIST Chemistry WebBook: Thermophysical properties of fluid systems \(https://webbook.nist.gov/chemistry/fluid/\)](https://webbook.nist.gov/chemistry/fluid/): Steam and refrigerant tables.
- [OpenStax UP2, 4.3 Refrigerators and heat pumps \(https://openstax.org/books/university-physics-volume-2/pages/4-3-refrigerators-and-heat-pumps\)](https://openstax.org/books/university-physics-volume-2/pages/4-3-refrigerators-and-heat-pumps): Free textbook section.
- [MIT OpenCourseWare 16.050 Thermal Energy \(Fall 2002\) \(https://ocw.mit.edu/courses/16-050-thermal-energy-fall-2002/\)](https://ocw.mit.edu/courses/16-050-thermal-energy-fall-2002/): Vapor cycle lectures.
- [NASA Glenn: Second law of thermodynamics \(https://www.grc.nasa.gov/www/k-12/airplane/thermo2.html\)](https://www.grc.nasa.gov/www/k-12/airplane/thermo2.html): Free NASA page.

☐ I finished this unit

The lab (Thermodynamics lab)

The lab is the hands-on part of the course. Here it is free and for practice only, with no credit.

Every lab can be done in a free simulation or with kitchen items. Hot water and steam scald: use oven mitts, keep the kettle on a stable counter, pour away from yourself, and keep children and pets clear. Never heat a sealed container.

Safety reference: [NFPA: Burn awareness information \(https://www.nfpa.org/education-and-research/home-fire-safety/burns\)](https://www.nfpa.org/education-and-research/home-fire-safety/burns)

Lab A: The ideal-gas law in PhET Gas Properties

WEEK 2

Goal: Show that pressure is proportional to absolute temperature at fixed volume and amount, and that pV/T stays constant.

$$\frac{p_1}{T_1} = \frac{p_2}{T_2} \quad (V, m \text{ fixed})$$

Ideal-gas law at constant volume

Procedure

1. Open PhET Gas Properties, Ideal tab; pump in gas and hold volume constant.
2. Heat the gas in steps and record T and p .
3. Plot p against T in kelvin; extend the line to $p = 0$.
4. Repeat at constant pressure and record volume.

Data table

T (K)	p (kPa), starting 100 kPa at 300 K
300	100
400	133.3
600	200

Ideal-gas values; the simulator's numbers fluctuate a little because it counts particle collisions.

Sample calculation

1. $p_2 = 100 \times 400/300 = 133.3$ kPa.
2. The line through the data passes through $p = 0$ at $T = 0$ K.

Safety

- Computer only.

Home or virtual alternative

- Gas Properties runs in a browser.

PhET: Gas Properties (<https://phet.colorado.edu/en/simulations/gas-properties>) · PhET: States of Matter (<https://phet.colorado.edu/en/simulations/states-of-matter>)

Planet link: DOE says reactor designers pressurize water so it does not boil; the same state relationships set every boiler and tank design. U.S. DOE: Nuclear 101: How does a nuclear reactor work? (May 2025) (<https://www.energy.gov/ne/articles/nuclear-101-how-does-nuclear-reactor-work>)



I completed this lab (wet or virtual)

Lab B: Kettle energy balance and efficiency

WEEK 5

Goal: Apply the first law to heating water and find how much of a kettle's electrical energy reaches the water.

$$\eta = \frac{mc\Delta T}{Pt}$$

Kettle efficiency

Procedure

1. Weigh 1.00 kg (1 L) of tap water and measure its temperature.
2. Read the kettle's power rating from its label.
3. Time how long it takes to reach boiling (the kettle switches off).
4. Compute the heat absorbed and the electrical energy used.

Data table

Quantity	Value
Water heat, 1 kg 20 → 100 °C (kJ)	334.4
Electrical energy, 1500 W × 250 s (kJ)	375.0
Efficiency	89.2%

Sample values; your kettle's time depends on its power, the water's starting temperature and your altitude.

Sample calculation

1. $Q = 1 \times 4.18 \times 80 = 334.4$ kJ.
2. $\eta = 334.4/375 = 89.2\%$.

Safety

- Steam and boiling water scald: keep the lid closed, pour away from yourself, and keep children and pets away.
- Do not touch the kettle body while hot.

Home or virtual alternative

- This is a home lab.

PhET: Energy Forms and Changes (<https://phet.colorado.edu/en/simulations/energy-forms-and-changes>)

Planet link: DOE notes resistance heating turns 1 kWh into 1 kWh of heat, while heat pumps cut electricity use by about 50%. [U.S. DOE: Pump up your savings with heat pumps \(May 30, 2023\)](https://www.energy.gov/articles/pump-your-savings-heat-pumps) (<https://www.energy.gov/articles/pump-your-savings-heat-pumps>)



I completed this lab (wet or virtual)

Lab C: Melting ice and latent heat

WEEK 5

Goal: Use a heat balance to predict the final temperature when ice melts in warm water, and compare with measurement.

$$m_w c(T_w - T_f) = m_i h_{if} + m_i c T_f$$

Heat lost by water = heat gained by ice

Procedure

1. Put 300 g of 40 °C water in an insulated cup.
2. Add 50 g of ice at 0 °C (pat it dry).
3. Stir gently until all the ice has melted and record the lowest temperature.
4. Compare with the predicted final temperature.

Data table

Quantity	Value
Water	0.300 kg at 40 °C
Ice	0.050 kg at 0 °C
Predicted final T	22.9 °C

Sample values; heat gained from the cup and air makes the measured value a little higher.

Sample calculation

1. $0.3 \times 4.18 \times (40 - T) = 0.05 \times 334 + 0.05 \times 4.18 \times T$.
2. $T = 33.46/1.463 = 22.9 \text{ °C}$.

Safety

- Use warm tap water, not boiling.

Home or virtual alternative

- This is a home lab.

PhET: States of Matter (<https://phet.colorado.edu/en/simulations/states-of-matter>) · PhET: Energy Forms and Changes (<https://phet.colorado.edu/en/simulations/energy-forms-and-changes>)

Planet link: Latent heat is how thermal storage works; DOE notes geothermal energy can also support thermal energy storage. [U.S. DOE: Geothermal basics \(https://www.energy.gov/eere/geothermal/geothermal-basics\)](https://www.energy.gov/eere/geothermal/geothermal-basics)



I completed this lab (wet or virtual)

Lab D: Insulation and cooling rate

WEEK 4

Goal: Compare how fast hot water cools in a plain and an insulated mug, and find each cooling constant.

$$\frac{T - T_{\infty}}{T_0 - T_{\infty}} = e^{-kt}$$

Newton's law of cooling

Procedure

1. Fill two mugs, one plain and one insulated (or wrapped in a towel), with water at about 80 °C.
2. Record temperature every 2 minutes for 20 minutes; note room temperature.
3. Compute $k = \ln[(T_0 - T_{\infty})/(T - T_{\infty})]/t$ for each.
4. Compare the heat-loss rates.

Data table

Mug	T after 20 min (°C)	k (1/min)
Plain	60	0.0203
Insulated	70	0.00912

Sample values with room at 20 °C.

Sample calculation

1. Plain: $k = \ln(60/40)/20 = 0.0203$ per minute.
2. Insulated: $k = \ln(60/50)/20 = 0.00912$ per minute, less than half.

Safety

- Hot water scalds: use oven mitts and keep mugs on a stable surface away from edges.

Home or virtual alternative

- This is a home lab.

PhET: Energy Forms and Changes (<https://phet.colorado.edu/en/simulations/energy-forms-and-changes>)

Planet link: DOE advises weatherizing before installing a heat pump, because insulation cuts the heat a home must replace. [U.S. DOE: Pump up your savings with heat pumps \(May 30, 2023\)](https://www.energy.gov/articles/pump-your-savings-heat-pumps) (<https://www.energy.gov/articles/pump-your-savings-heat-pumps>)



I completed this lab (wet or virtual)

Lab E: Carnot limits for a heat pump

WEEK 8

Goal: Build a spreadsheet of the Carnot COP of a heat pump against outdoor temperature and compare with a real unit's rated COP.

$$COP_{HP,Carnot} = \frac{T_H}{T_H - T_L}$$

Carnot heat pump

Procedure

1. Set indoor $T_H = 294$ K.
2. List outdoor temperatures from 253 K to 288 K.
3. Compute the Carnot COP for each.
4. Look up the rated efficiency of any heat pump on its label or ENERGY STAR listing and compare.

Data table

T _L (K)	COP _{Carnot}
263	9.48
273	14.0
283	26.7

Ideal limits; real heat pumps reach a fraction of these.

Sample calculation

1. $COP = 294 / (294 - 263) = 9.48$.
2. Colder outdoor air means a lower limit.

Safety

- Computer only.

Home or virtual alternative

- Any spreadsheet works.

OpenStax UP2, 4.3 Refrigerators and heat pumps (<https://openstax.org/books/university-physics-volume-2/pages/4-3-refrigerators-and-heat-pumps>)

Planet link: DOE says geothermal heat pumps, using steady ground temperatures, can cut energy use by 30% to 60%. U.S. DOE: Pump up your savings with heat pumps (May 30, 2023) (<https://www.energy.gov/articles/pump-your-savings-heat-pumps>)



I completed this lab (wet or virtual)

Lab F: Rankine cycle spreadsheet

WEEK 15

Goal: Compute an ideal Rankine cycle from steam-table values and see how the turbine, pump and boiler terms set efficiency.

$$\eta = \frac{(h_3 - h_4) - v_1(p_2 - p_1)}{h_3 - h_2}$$

Ideal Rankine efficiency

Procedure

1. Look up the four states in NIST's WebBook (or use the values given).
2. Compute pump work, heat in, turbine work, net work and η .
3. Change the condenser pressure or boiler temperature using new table values and recompute.
4. Find the steam flow for a 100 MW plant.

Data table

Quantity	Value
w_pump (kJ/kg)	3.03
q_in (kJ/kg)	2728.6
w_net (kJ/kg)	710.1
η	26.0%

Steam-table values for 3 MPa/350 °C and 75 kPa.

Sample calculation

1. $\eta = 710.1/2728.6 = 26.0\%$.
2. Steam flow for 100 MW = $100,000/710.1 = 140.8$ kg/s.

Safety

- Computer only.

Home or virtual alternative

- Any spreadsheet works.

NIST Chemistry WebBook: Thermophysical properties of fluid systems (<https://webbook.nist.gov/chemistry/fluid/>)

Planet link: DOE says nuclear and geothermal plants both turn heat into steam that spins turbines, the cycle in this lab. [U.S. DOE: Nuclear 101: How does a nuclear reactor work? \(May 2025\)](https://www.energy.gov/ne/articles/nuclear-101-how-does-nuclear-reactor-work) (<https://www.energy.gov/ne/articles/nuclear-101-how-does-nuclear-reactor-work>) · [U.S. DOE: Geothermal basics](https://www.energy.gov/eere/geothermal/geothermal-basics) (<https://www.energy.gov/eere/geothermal/geothermal-basics>)



I completed this lab (wet or virtual)

Exam prep practice sets

Time yourself: about 10 minutes per problem. Then compare with the full solutions.

Midterm practice set (Units 1–5)

1. A plant has a heat rate of 8530 Btu/kWh. Find its efficiency.

1. $3412/8530$.

Answer: 40.0%.

2. Find the mass of air in a 2 m³ tank at 200 kPa and 350 K.

1. $m = 200 \times 2 / (0.287 \times 350)$.

Answer: 3.98 kg.

3. Find h at 100 kPa and quality 0.9 ($h_f = 417.51$, $h_{fg} = 2257.5$ kJ/kg).

1. $417.51 + 0.9 \times 2257.5$.

Answer: 2449.3 kJ/kg.

4. 3 kg of water is heated from 15 °C to 65 °C. Find Q .

1. $3 \times 4.18 \times 50$.

Answer: 627 kJ.

5. Steam at 10 kg/s drops 800 kJ/kg in an adiabatic turbine. Find the power.

1. 10×800 .

Answer: 8000 kW.

Final practice set (all units)

1. Find the Carnot efficiency between 900 K and 300 K.

$$1. 1 - 300/900.$$

Answer: 66.7%.

2. A heat pump delivers 12 kW with COP 4. Find the electrical power and the heat taken from outside.

$$1. W = 12/4; Q_L = 12 - 3.$$

Answer: 3 kW and 9 kW.

3. Find Δs of 1 kg of air from 300 K, 100 kPa to 600 K, 100 kPa.

$$1. 1.005 \ln 2.$$

Answer: 0.697 kJ/(kg·K).

4. Find the exergy of 500 kJ of heat at 1000 K with $T_0 = 300$ K.

$$1. 500 \times 0.7.$$

Answer: 350 kJ.

5. Find the Otto efficiency at $r = 9$.

$$1. 1 - 9^{(-0.4)}.$$

Answer: 58.5%.

6. A refrigeration cycle has $q_L = 150$ kJ/kg and $w = 37.5$ kJ/kg. Find COP_R and COP_{HP}.

$$1. 150/37.5.$$

Answer: 4.0 and 5.0.

Formula sheet

$$\eta = 3412/\text{heat rate}, v = V/m$$

$$pv = RT, y = y_f + x y_{fg}$$

$$W_b = \int p dV, W = mRT \ln(V_2/V_1)$$

$$Q - W = \Delta U, h = u + pv$$

$$\Delta u = c_v \Delta T, \Delta h = c_p \Delta T, Q = mc \Delta T$$

$$\dot{Q} - \dot{W} = \dot{m}(\Delta h + \Delta V^2/2 + g \Delta z)$$

$$\eta = W/Q_H, COP_R = Q_L/W, COP_{HP} = Q_H/W$$

$$\eta_{Carnot} = 1 - T_L/T_H$$

$$\Delta s = c_p \ln(T_2/T_1) - R \ln(p_2/p_1)$$

$$T_2/T_1 = (p_2/p_1)^{(k-1)/k}$$

$$X_Q = Q(1 - T_0/T), I = T_0 S_{gen}$$

$$\eta_{Otto} = 1 - r^{1-k}, \eta_{Brayton} = 1 - r_p^{(1-k)/k}$$

$$w_p = v \Delta p, COP_R = (h_1 - h_4)/(h_2 - h_1)$$

Constants

Constant	Value
Universal gas constant	R_u = 8.314 kJ/(kmol·K)
Air (ideal gas, room temperature, textbook values)	R = 0.287 kJ/(kg·K), c_p = 1.005, c_v = 0.718 kJ/(kg·K), k = 1.4
Liquid water (textbook value)	c = 4.18 kJ/(kg·K)
Latent heats (textbook values)	fusion of ice 334 kJ/kg; vaporization at 100 °C 2257 kJ/kg
Energy units	1 kWh = 3600 kJ; 1 Btu = 1.055 kJ; 1 kWh = 3412 Btu
Absolute temperature	T(K) = T(°C) + 273.15

Source: NIST: CODATA value of the molar gas constant (<https://physics.nist.gov/cgi-bin/cuu/Value?r>)

Free texts, data and simulations

Use these free lectures, property data and simulations alongside the course.

- MIT OpenCourseWare 16.050 Thermal Energy (Fall 2002) (<https://ocw.mit.edu/courses/16-050-thermal-energy-fall-2002/>): Free MIT lecture notes and problems.
- MIT OpenCourseWare 16.01–16.04 Unified Engineering (2005–2006) (<https://ocw.mit.edu/courses/16-01-unified-engineering-i-ii-iii-iv-fall-2005-spring-2006/>): Free MIT thermodynamics notes.
- OpenStax University Physics Volume 2, Chapter 3: The first law of thermodynamics (<https://openstax.org/books/university-physics-volume-2/pages/3-introduction>): Free textbook chapter.
- OpenStax University Physics Volume 2, Chapter 4: The second law of thermodynamics (<https://openstax.org/books/university-physics-volume-2/pages/4-introduction>): Free textbook chapter.
- NIST Chemistry WebBook: Thermophysical properties of fluid systems (<https://webbook.nist.gov/chemistry/fluid/>): Free steam and refrigerant property tables.
- PhET: Gas Properties (<https://phet.colorado.edu/en/simulations/gas-properties>): Pressure, volume, temperature interactively.

Glossary

Adiabatic

No heat transfer.

Back-work ratio

Compressor work over turbine work.

COP

Coefficient of performance of a refrigerator or heat pump.

Carnot cycle

Reversible cycle between two reservoirs; the best possible.

Control volume

Region in space that mass can cross.

Dead state

Equilibrium with the surroundings.

Enthalpy

$h = u + pv$.

Entropy

Property with $dS = \delta Q_{\text{rev}}/T$; measures irreversibility.

Exergy

Maximum useful work obtainable.

Heat engine

Device that converts heat to work in a cycle.

Heat pump

Device that moves heat from cold to hot using work.

Heat rate

Fuel Btu per kWh generated.

Isentropic

Constant entropy; reversible and adiabatic.

Latent heat

Energy for phase change at constant temperature.

Quality

Vapor mass fraction of a saturated mixture.

Rankine cycle

Steam power cycle: pump, boiler, turbine, condenser.

Reversible process

Idealized process with no entropy generation.

Saturation

State where liquid and vapor coexist.

Specific heat

Energy to raise 1 kg by 1 K.

Throttling

Pressure drop at constant enthalpy.

Self-assessment rubric

No grade or credit is given. Use this to judge honestly where you are in each unit.

Level	What it looks like
4 · Mastery	Draws systems and diagrams, looks up states correctly, writes complete mass, energy and entropy balances, checks against Carnot limits, and runs labs safely.
3 · Proficient	Solves the practice problems with occasional table or unit slips.
2 · Developing	Follows worked examples but mixes up open and closed systems, or uses °C in ratios.
1 · Beginning	Plugs numbers into formulas without a system sketch; needs to revisit the unit.

Suggested weighting if you want a score

Part	Weight
Practice problems	20%
Labs	25%
Midterm practice set	25%
Final practice set	30%

Aim for level 3 or better in every unit before moving to the next course.

Related courses

- [Aerodynamics I](#) AERO 310
- [All courses](#)